



PORT OF GUAM
ATURIDAT / PUETTON GUAHAN
Jose D. Leon Guerrero Commercial Port
1026 Cabras Highway, Suite 201, Piti, Guam 96915
Telephone: 671-477-5931/35 Facsimile: 671-477-2689/4445
Website: www.portguam.com



Lourdes A. Leon Guerrero
Governor of Guam
Joshua F. Tenorio
Lieutenant Governor

INVITATION FOR BID No.: IFB/PAG-001-26

DESCRIPTION:

Lubricant and Degreasers Bid

AMENDMENT NO. 1

DATE: Thursday, January 29, 2026

ALL PROPOSERS MUST ACKNOWLEDGE RECEIPT OF THIS AMENDMENT ON AREA PROVIDED BELOW AND RETURN COPY TO PAG PROCUREMENT OFFICE: Fax: (671) 472-1439 or Email: Kirida H. Charfauros at khcharfauros01@portofguam.com and PAG Procurement at pagprocurement@portofguam.com

NOTICE TO OFFERORS: The IFB Documents of the above-referenced project are to be included as part of the bid packet:

- 1. Amend to replace page 39 of 39 with revised 1/29/26 page 39 of 39.**

***** END OF AMENDMENT NO. 1 *****

Issued By:

RORY J. RESPICIO

General Manager

NAME OF PROPOSER: _____

AUTHORIZED SIGNATURE: _____

PRINT NAME: _____

DATE: _____ **TIME:** _____

cc: Procurement Record IFB-PAG-001-26, Amendment No. 1

Port of Guam, Jose D. Leon Guerrero Commercial Port is an Equal Employment Opportunity Employer.
Complaints of discrimination should be sent to the Human Resources Division.

REQUIRED DELIVERY DATE: 30 DAYS FROM RECEIPT OF PURCHASE ORDER FOR A PERIOD OF ONE (1) YEAR UPON THE AVAILABILITY OF FUNDS.

NOTES:

1. All Lubricants must meet or exceed Specification as shown.
2. All Lubricants must be new and unused (virgin stock). Corroded or damaged drums are not acceptable.
3. Unit of Measure "DR" refers to 55-gallon drum or 120-pound drum.
4. All containers must be factory sealed without leakage and filled accordingly.
5. Bid Item No. 6 above must have OEM Allison TES-295 approval number and approved logo.
6. Bid Item No. 7 above, NOTE: Mercon and Dexron are totally different from "MERCON V".
7. Dexron III-H and Mercon are not equivalent to "MERCON V".
8. Bid Item No. 16 above must include on (1) each plastic drum pump and four (4) each quart size spray bottles with trigger.
9. All Lubricants to be delivered to PAG must include the Safety Data Sheet (SDS).

DEFINITIONS:

- **AFMT** Anti-Friction Metal Treatment
- **API** American Petroleum Institute
- **ASTM** American Society for Testing & Materials for heavy duty diesel engines
- **CH-4** API service category for diesel engines introduced in 1998
- **Dexron III (H)** OEM General Motors specification for transmission fluid
- **GL-5** API service category for gear oil
- **ISO VG** Viscosity grade system for hydraulic oils, introduced by International Organization For Standardization.
- **SAE** Society of Automotive Engineers

THE ABOVE SPECIFICATIONS WERE DEVELOPED BY THE PORT AUTHORITY OF GUAM EQUIPMENT MAINTENANCE DIVISION: JULIE S. KABILIING, GUS AROMIN, JOHN J. LEON GUERRERO, SHINE SAN AGUSTIN, AND JOAQUIN P. PANGELINAN, REVIEWED BY ANNIE L.G. SABLAM AND APPROVED BY THE GENERAL MANAGER - RORY J. RESPICIO.

THESE SPECIFICATIONS WERE DERIVED AND COMPILED BASED ON RESEARCH OF INDUSTRY AVAILABILITY, RESPONSES TO SURVEY QUESTIONNAIRES, AND TECHNICAL LITERATURE RECEIVED FROM VENDORS(S).